

Qty. Description

1 CR 2-60 A-A-A-AUUE



Note! Product picture may differ from actual product

Product No.: [40750006](#)

Vertical, non-self-priming, multistage, in-line, centrifugal pump for installation in pipe systems and mounting on a foundation.

The pump has the following characteristics:

- Impellers and intermediate chambers are made of

Impeller: Stainless steel DIN W.-Nr. EN 1.4301.

Pump housing: - Pump head and base are made of Cast iron.

- The shaft seal has assembly length

according to EN 12756.

- Power transmission is via cast iron split

coupling.

Flange standard: - Pipework connection is via OVAL flanges.

Liquid:

Pumped liquid: Water

Liquid temperature range: -15 .. 120 °C

Selected liquid temperature: 20 °C

Density: 998.2 kg/m³

Technical:

Pump speed on which pump data are based: 2900 rpm

Rated flow: 2.5 m³/h

Rated head: 37.7 m

Code for shaft seal: AUUE

Materials:

Base: Cast iron
EN-JL1030
25 B

Impeller: Stainless steel
EN 1.4301
AISI 304

Installation:

Max pressure at stated temp: 16 bar / 120 °C

Type of connection: OVAL

Size of inlet connection: Rp 1

Flange size for motor: F100

Electrical data:

Power (P2) required by pump: 0.75 kW

Others:



Company name:

Created by:

Phone:

Date:

04/02/2021

Qty.	Description
	Net weight: 15 kg